

GOXR-L

Economical Full-Featured
Radiographic Room



Fully Integrated

Compact Design

4 Way Table (6 way optional)

Recessed Foot-Pedals

Wall Stand Lowers to Below 10"

The XRGO-L is a full-featured radiographic room that comes standard with the Rayence's 1417WCC DR system which is fully integrated with the generator controls and all DR and generator functions can be controlled from the large touch screen workstation display with the Xmaru Pro software.



4 way



6 way

4 Way / 6 Way Elevating Table

The compact size and modular design allows us to fit in rooms that offer limited space and the ability to configure the system with either a compact 4 way floating top or optional 6 way elevating top table. The table offers 10" transverse travel, 32" longitudinal travel and a minimum height of 31" for the 4 way and 22" minimum height for the 6 way.



The long vertical travel of both the wall stand and tube arm facilitate a full range of exams including weight-bearing studies and the ergonomically designed handle allows for easy positioning of the wall stand receptor



The single large foot pedal release simplifies movement and locking of tabletop



Cross table exams are easily performed using the +/- 180 degree rotational and +/- 5" transverse positioning capability

	Descriptions	Technical Specifications
DETECTOR	Model	1417WCC
TUBE STAND	Style	floor to wall or ceiling
	Rail length	8 ft rail or 10 ft rail
	Transverse travel	plus / minus 5" travel
	Long Travel of Focal Spot	75.7" w/ 8ft rail, 99.7" w/ 10ft rail
	Display	angulation dial, handgrips, electric locks
	Vertical Travel Range	76.8" max, 76.4-76.9 trunnion, 13.5 beam horizontal
	Wall to focal spot at detent position	39.2" platform, 40.3" trunnion ring
	Tube Rotation	180 degrees 90 degrees detents
WALL STAND	Model	S109
	Vertical Travel Range	9.75" - 72.75"
	Left or Right Hand Load Bucky	yes
TUBE	Model	E411
	Tube Focal Spot	.6-1.5 focal, 200 KHU
COLLIMATOR	Model	5658
	Style	LED , 150kVp w/ swivel mount
	Features	laser bucky light and tape measure
GENERATOR	Generator Power Output	421/3e, 42kW high freq
	mA range	25-500mA
	Power	205/250-1 phase 208/408-3 phase
	mAs range	0.1-600mAs
TABLE	Model	S210
	Movement	four way float
	Vertical travel	none
	Transverse/Long Travel	10" transverse, 32" longitudinal
	Dimensions	84"x30.5", table height 31.5"
	Grid	103LP, 10:1
	OPTION	Option
	Table travel	22"-33"
	Transverse travel	plus or minus 5"
	Longitudinal travel	32"
	Weight Capacity	400 lbs
ROOM	Min. Required	12'6" x 11' x 9'